

[HTC-36] CNC Lathe Machine



Accessories

GSK999TA controller
Imported ball screw, linear guide way, bearings
Taiwan 8" hydraulic chuck
Taiwan 8 position hydraulic turret
Chip tray
Automatic center lubrication

Technical Specifications

Max. swing dia. over bed	mm	500
Max. cutting length	mm	500
Max. cutting dia.	mm	360
Max. swing dia. over carriage	mm	320
Spindle nose		A2-6
Spindle dia.	mm	65
Spindle speed	rpm	50-4500
Main motor	kw	11
X/Z rapid speed	m/min	30/30
X/Z travel	mm	200/550
Tailstock unit travel	mm	450
Tailstock sleeve travel	mm	100
Tailstock taper		5#
Machining accuracy		IT6
X/Z position accuracy	mm	0.008
X/Z repeatability position accuracy	mm	0.004
Machining roughness	Ra	1.25µm
Machine size	mm	2300*1700*1930

*Products and specifications subject to change without notice.

*The product images shown are for illustration purposes only and may not be an exact representation of the product.

*Aciera reserves the right to change product images and specifications at any time without notice.

PT. BUANA PRIMA RAYA

Jakarta Office:

Ruko Mega Grosir Cempaka Mas Blok L No.38

Jl. Letjen. Suprpto

Jakarta Pusat 10640

Phone: (021) 424 4000, 888 50712

Fax: (021) 889 2116

Email: bpr@centrin.net.id, sales@buanaprimaraya.com

www.buanaprimaraya.com

Bekasi Office:

Gedung Grha Bekasi Bagus

Jl. KH Noer Ali no. 89

Bekasi Selatan 17144

Phone: (021) 2851 9161, 888 60531

